



Suspension Glass Downlight 110 Black Rod 100 mm On Board Dimmer

■ 03.8130.00 - Transparent Glass


Suspended luminaire with rigid rod and blown glass in several finishes to be installed in the Infra-Structure system.

Main specifications

| | | | |
|------------------|-------|----------------|---------------------|
| Number of heads | 1 | CRI | 90 |
| Lamp category | LED | Net lumen (lm) | 706 |
| Power (W) | 13.5W | Mountings | Track |
| System power (W) | 14 | Environment | Indoor dry location |
| CCT (K) | 2700K | | |

Optical

| | |
|------------------------|----------------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Diffused light |
| Beam angle (°) | 82 |
| Beam angle C90-270 (°) | 82 |
| Efficiency (lm/W) | 50.43 |



| | | | |
|-------------|------|-------|------|
| Beam Angle: | 82° | | |
| | h(m) | E(lx) | D(m) |
| 1 | 449 | 1.74 | |
| 2 | 112 | 3.48 | |
| 3 | 50 | 5.22 | |
| 4 | 28 | 6.96 | |
| 5 | 18 | 8.71 | |

Luminous flux luminaire
706 lm



Electrical

| | | | |
|-------------|-----------------|------------------|-----|
| Voltage (V) | 48 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote excluded | | |
| Driver type | Dimmer on board | | |
| Emergency | Without | | |

Physical

| | |
|--------------------|-------------|
| Color | Transparent |
| | Glass |
| Orientation | Fixed |
| Weight (kg) | 0.98 |
| Length (mm) | 205 |
| Lifespan (L70 B10) | L80B50 |

