



Suspension Glass Downlight 110 Black Rod 100 mm On Board Dimmer

03.8130.FU - Smoked Glass

Suspended luminaire with rigid rod and blown glass in several finishes to be installed in the Infra-Structure system.


Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 483 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 13.5W | Environment | Indoor dry location |
| CCT (K) | 2700K | | |
| CRI | 90 | | |



Optical

| | |
|-------------------------------|------------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Wide flood |
| Beam angle (°) | 47 |
| Beam angle C90-270 (°) | 47 |



Beam Angle: 47°

h(m) E(lx) D(m)

1 449 0.86

2 112 1.72

3 50 2.58

4 28 3.45

5 18 4.31

Luminous flux luminaire
483 lm

Electrical

| | | | |
|--------------------|-----------------|-------------------------|-----|
| Voltage (V) | 48.00 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote excluded | | |
| Driver type | Dimmer on board | | |
| Emergency | Without | | |

Physical

| | |
|--------------------|--------------|
| Color | Smoked Glass |
| Orientation | Fixed |
| Weight (kg) | 0.98 |
| Length (mm) | 205 |

