



Suspension Glass Downlight 110 Black Rod 400 mm Casambi integrated

New

03.8131.FU.CB - Smoked Glass


Suspended luminaire with rigid rod and blown glass in several finishes to be installed in the Infra-Structure system.

Main specifications

Number of heads	1	Net lumen (lm)	483
Lamp category	LED	Mountings	Track
Power (W)	13.5W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Optical


Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	47
Beam angle C90-270 (°)	47



Beam Angle: 47°

h(m)	E(lx)	D(m)
1	449	0.86
2	112	1.72
3	50	2.58
4	28	3.45
5	18	4.31

Luminous flux luminaire
483 lm



Electrical

Voltage (V)	48.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable		
Emergency	Casambi		
	Without		

Physical

Color	Smoked Glass
Orientation	Fixed
Weight (kg)	1.18
Length (mm)	205

Note

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

