



Suspension Glass Downlight 110 Black Rod 400 mm Dali Version

■ 03.8131.00.DA - Transparent Glass


Suspended luminaire with rigid rod and blown glass in several finishes to be installed in the Infra-Structure system.

Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	706
Power (W)	13.5W	Mountings	Track
System power (W)	14	Environment	Indoor dry location
CCT (K)	2700K		

Optical


Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	82
Beam angle C90-270 (°)	82
Efficiency (lm/W)	50.43



Beam Angle: 82°

	h(m)	E(lx)	D(m)
1	449	1.74	
2	112	3.48	
3	50	5.22	
4	28	6.96	
5	18	8.71	

Luminous flux luminaire
706 lm



Electrical

Voltage (V)	48	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable DALI		
	1		
Emergency	Without		

Physical

Color	Transparent
	Glass
Orientation	Fixed
Weight (kg)	1.18
Length (mm)	205
Lifespan (L70 B10)	L80B50

Note

Only compatible with DALI profile version.

