



Suspension Glass Downlight 110 Black Rod 400 mm Dali Version

■ 03.8133.RC.DA - Red Glass

Suspended luminaire with rigid rod and blown glass in several finishes to be installed in the Infra-Structure system.


Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 309 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 13.5W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |



Optical

| | |
|-------------------------------|------------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Wide flood |
| Beam angle (°) | 42 |
| Beam angle C90-270 (°) | 42 |



| | | | |
|--------------------|-------------|--------------|-------------|
| Beam Angle: | 42° | | |
| | h(m) | E(lx) | D(m) |
| 1 | 459 | 0.76 | |
| 2 | 115 | 1.52 | |
| 3 | 51 | 2.28 | |
| 4 | 29 | 3.04 | |
| 5 | 18 | 3.80 | |

Luminous flux luminaire
309 lm

Electrical

| | | | |
|--------------------|-----------------|-------------------------|-----|
| Voltage (V) | 48.00 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote excluded | | |
| Driver type | Dimmable DALI | | |
| | 1 | | |
| Emergency | Without | | |

Physical

| | |
|--------------------|-----------|
| Color | Red Glass |
| Orientation | Fixed |
| Weight (kg) | 1.18 |
| Length (mm) | 205 |

Note

Only compatible with DALI profile version.

