



## Suspension Glass Downlight 110 Black Rod 400 mm Dimmable 1-10V

■ 03.8133.00.1V - Transparent Glass


Suspended luminaire with rigid rod and blown glass in several finishes to be installed in the Infra-Structure system.

### Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	746
Power (W)	13.5W	Mountings	Track
System power (W)	14	Environment	Indoor dry location
CCT (K)	3000K		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	82
Beam angle C90-270 (°)	82
Efficiency (lm/W)	53.29



Beam Angle:	82°		
	h(m)	E(lx)	D(m)
1	474	1.74	
2	119	3.48	
3	53	5.22	
4	30	6.96	
5	19	8.71	

Luminous flux luminaire  
746 lm



### Electrical

Voltage (V)	48	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable 1-10V		
Emergency	Without		

### Physical

Color	Transparent Glass
Orientation	Fixed
Weight (kg)	1.18
Length (mm)	205
Lifespan (L70 B10)	L80B50

### Note

Only compatible with 1-10V profile version.

