



## Suspension Glass Downlight 110 White Rod 100 mm Dali Version

03.8137.FU.DA - Smoked Glass


Suspended luminaire with rigid rod and blown glass in several finishes to be installed in the Infra-Structure system.

### Main specifications

<b>Number of heads</b>	1	<b>CRI</b>	90
<b>Lamp category</b>	LED	<b>Net lumen (lm)</b>	510
<b>Power (W)</b>	13.5W	<b>Mountings</b>	Track
<b>System power (W)</b>	14	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		


### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Wide flood
<b>Beam angle (°)</b>	47
<b>Beam angle C90-270 (°)</b>	47
<b>Efficiency (lm/W)</b>	36.43



<b>Beam Angle:</b>	47°		
	<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	474	0.86	
2	119	1.72	
3	53	2.58	
4	30	3.45	
5	19	4.31	

Luminous flux luminaire  
510 lm



### Electrical

<b>Voltage (V)</b>	48	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote excluded		
<b>Driver type</b>	Dimmable DALI		
	1		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Smoked Glass
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	0.98
<b>Length (mm)</b>	205
<b>Lifespan (L70 B10)</b>	L80B50

### Note

Only compatible with DALI profile version.

