



## Suspension Glass Downlight 110 White Rod 100 mm Dimmable 1-10V

03.8137.FU.1V - Smoked Glass

Suspended luminaire with rigid rod and blown glass in several finishes to be installed in the Infra-Structure system.


### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	510
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	13.5W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		



### Optical


<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Wide flood
<b>Beam angle (°)</b>	47
<b>Beam angle C90-270 (°)</b>	47



Beam Angle: 47°

h(m)	E(lx)	D(m)
1	474	0.86
2	119	1.72
3	53	2.58
4	30	3.45
5	19	4.31

Luminous flux luminaire  
510 lm



### Electrical

<b>Voltage (V)</b>	48.00	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote excluded		
<b>Driver type</b>	Dimmable 1-10V		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Smoked Glass
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	0.98
<b>Length (mm)</b>	205

### Note

Only compatible with 1-10V profile version.

