



## Suspension Glass Downlight 110 White Rod 100 mm On Board Dimmer

03.8135.FU - Smoked Glass

Suspended luminaire with rigid rod and blown glass in several finishes to be installed in the Infra-Structure system.


### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	483
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	13.5W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		



### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Wide flood
<b>Beam angle (°)</b>	47
<b>Beam angle C90-270 (°)</b>	47



Beam Angle: 47°

h(m) E(lx) D(m)

1 449 0.86

2 112 1.72

3 50 2.58

4 28 3.45

5 18 4.31

Luminous flux luminaire  
483 lm

### Electrical

<b>Voltage (V)</b>	48.00	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote excluded		
<b>Driver type</b>	Dimmer on board		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Smoked Glass
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	0.98
<b>Length (mm)</b>	205

