

## Suspension Glass Downlight 110 White Rod 400 mm Casambi integrated

New

### 03.8136.RC.CB - Red Glass


Suspended luminaire with rigid rod and blown glass in several finishes to be installed in the Infra-Structure system.

### Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	292
Power (W)	13.5W	Mountings	Track
System power (W)	14	Environment	Indoor dry location
CCT (K)	2700K		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	42
Beam angle C90-270 (°)	42
UGRL	15
Efficiency (lm/W)	20.86



Beam Angle: 42°

h(m)	E(lx)	D(m)
1	435	0.76
2	109	1.52
3	48	2.28
4	27	3.04
5	17	3.80

Luminous flux luminaire  
292 lm

### Electrical

Voltage (V)	48	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable		
Emergency	Casambi		
	Without		

### Physical

Color	Red Glass
Orientation	Fixed
Weight (kg)	1.18
Length (mm)	205
Lifespan (L70 B10)	L80B50

### Note

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

