



Suspension Glass Downlight 110 White Rod 400 mm Dimmable 1-10V

■ 03.8138.00.1V - Transparent Glass

Suspended luminaire with rigid rod and blown glass in several finishes to be installed in the Infra-Structure system.


Main specifications

| | | | |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 746 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 13.5W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |



Optical

| | |
|------------------------|----------------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Diffused light |
| Beam angle (°) | 82 |
| Beam angle C90-270 (°) | 82 |



| | | | |
|-------------|------|-------|------|
| Beam Angle: | 82° | | |
| | h(m) | E(lx) | D(m) |
| 1 | 474 | 1.74 | |
| 2 | 119 | 3.48 | |
| 3 | 53 | 5.22 | |
| 4 | 30 | 6.96 | |
| 5 | 19 | 8.71 | |

Luminous flux luminaire
746 lm

Electrical

| | | | |
|-------------|-----------------|------------------|-----|
| Voltage (V) | 48.00 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote excluded | | |
| Driver type | Dimmable 1-10V | | |
| Emergency | Without | | |

Physical

| | |
|-------------|-------------|
| Color | Transparent |
| | Glass |
| Orientation | Fixed |
| Weight (kg) | 1.18 |
| Length (mm) | 205 |

Note

Only compatible with 1-10V profile version.

