



## Suspension Glass Downlight 110 White Rod 400 mm On Board Dimmer

■ 03.8138.FU - Smoked Glass


Suspended luminaire with rigid rod and blown glass in several finishes to be installed in the Infra-Structure system.

### Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	510
Power (W)	13.5W	Mountings	Track
System power (W)	14	Environment	Indoor dry location
CCT (K)	3000K		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	47
Beam angle C90-270 (°)	47
Efficiency (lm/W)	36.43



Beam Angle:	47°		
	h(m)	E(lx)	D(m)
1	474	0.86	
2	119	1.72	
3	53	2.58	
4	30	3.45	
5	19	4.31	

Luminous flux luminaire  
510 lm



### Electrical

Voltage (V)	48	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmer on board		
Emergency	Without		

### Physical

Color	Smoked Glass
Orientation	Fixed
Weight (kg)	1.18
Length (mm)	605
Lifespan (L70 B10)	L80B50

