

## Suspension Panel 600

New

03.8450.40 - White

Suspended luminaire with locking system integrated, to be installed in the Infra-Structure Episode 2 system.




### Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	1529
Power (W)	35.5W	Mountings	Ceiling surface
System power (W)	40	Environment	Indoor dry location
CCT (K)	2700K		

### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	113
Beam angle C90-270 (°)	113
UGRL	19
Efficiency (lm/W)	38.22



Beam Angle: 113°

h(m)	E(lx)	D(m)
1	534	3.02
2	134	6.04
3	59	9.06
4	33	12.08
5	21	15.10

Luminous flux luminaire  
1529 lm

### Electrical



Dimmable	Yes
Driver	Remote excluded
Emergency	Without
Insulation class	III

### Physical

Color	White
Orientation	Fixed
Weight (kg)	4.96
Spot diameter (mm)	600
Lifespan (L70 B10)	L80B50

### Note

Each lighting element is completed by a long 4m electrical cable equipped with an output microconnector.




# Suspension Panel 600



LED Power Supply Source for remote installation. 48V. 100Vac (150W)-240Vac (200W)  
60.9607



LED Power Supply Source for remote installation. 48V/320W. 100/240 Vac  
60.8919



Casambi Controller 220-240V. Remote Installation  
60.9392



LED power supply source for remote installation, 48V/120W. 220/240 Vac  
60.9170



DALI 12-48V Dimmer  
60.9678



0/1-10V & Push 12-48V Dimmer  
60.9395