

Suspension Panel 600

New

03.8451.14 - Black

Suspended luminaire with locking system integrated, to be installed in the Infra-Structure Episode 2 system.




Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	1229
Power (W)	35.5W	Mountings	Ceiling surface
System power (W)	40	Environment	Indoor dry location
CCT (K)	3000K		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	113
Beam angle C90-270 (°)	113
UGRL	19
Efficiency (lm/W)	30.73



Beam Angle: 113°

h(m)	E(lx)	D(m)
1	430	3.02
2	107	6.03
3	48	9.05
4	27	12.07
5	17	15.09

Luminous flux luminaire
1229 lm

Electrical



Dimmable	Yes
Driver	Remote excluded
Emergency	Without
Insulation class	III

Physical

Color	Black
Orientation	Fixed
Weight (kg)	4.96
Spot diameter (mm)	600
Lifespan (L70 B10)	L80B50

Note

Each lighting element is completed by a long 4m electrical cable equipped with an output microconnector.



Suspension Panel 600



LED Power Supply Source for remote installation. 48V. 100Vac (150W)-240Vac (200W)
60.9607



DALI 12-48V Dimmer
60.9678



Casambi Controller 220-240V. Remote Installation
60.9392



LED power supply source for remote installation, 48V/120W. 220/240 Vac
60.9170



LED Power Supply Source for remote installation. 48V/320W. 100/240 Vac
60.8919



0/1-10V & Push 12-48V Dimmer
60.9395