

Suspension Panel 600 Rod 100 mm Dali Version

■ 03.8140.14.DA - Black/Gold

Suspended luminaire with rigid rod, to be installed in the Infra-Structure system.




Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	1486
Power (W)	40W	Mountings	Track
System power (W)	40	Environment	Indoor dry location
CCT (K)	2700K		

Optical


Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	114
Beam angle C90-270 (°)	114
UGRL	20
Efficiency (lm/W)	37.15



Beam Angle: 114°

h(m)	E(lx)	D(m)
1	516	3.06
2	129	6.11
3	57	9.17
4	32	12.22
5	21	15.28

Luminous flux luminaire
1486 lm



Electrical

Voltage (V)	48	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable DALI		
	1		
Emergency	Without		

Physical

Color	Black/Gold
Orientation	Fixed
Weight (kg)	4.96
Length (mm)	605
Lifespan (L70 B10)	L80B50

Note

Only compatible with DALI profile version.

