

Suspension Panel 600 Rod 100 mm On Board Dimmer

03.8140.40 - White/White

Suspended luminaire with rigid rod, to be installed in the Infra-Structure system.




Main specifications

| | | | |
|------------------------|-------|-----------------------|--------|
| Number of heads | 1 | Net lumen (lm) | 1529 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 40W | Environment | Indoor |
| CCT (K) | 2700K | | |
| CRI | 90 | | |

Optical


| | |
|-------------------------------|----------------|
| Lighting type | Direct |
| LED type | Top LED |
| Light distribution | Symmetric |
| Optical type | Diffused light |
| Beam angle (°) | 113 |
| Beam angle C90-270 (°) | 113 |



Beam Angle: 113°

| h(m) | E(lx) | D(m) |
|------|-------|-------|
| 1 | 534 | 3.02 |
| 2 | 134 | 6.04 |
| 3 | 59 | 9.06 |
| 4 | 33 | 12.08 |
| 5 | 21 | 15.10 |

Luminous flux luminaire
1529 lm



Electrical

| | |
|-------------------------|---------|
| Voltage (V) | 48.00 |
| Dimmable | Yes |
| Driver | Remote |
| Emergency | Without |
| Insulation class | III |

Physical

| | |
|--------------------|-------------|
| Color | White/White |
| Orientation | Fixed |
| Weight (kg) | 4.96 |
| Length (mm) | 605 |

