


Suspension Panel 600 Rod 400 mm Casambi integrated

New

03.8141.40.CB - White/White

Suspended luminaire with rigid rod, to be installed in the Infra-Structure system.




Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	1529
Power (W)	40W	Mountings	Track
System power (W)	40	Environment	Indoor dry location
CCT (K)	2700K		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	113
Beam angle C90-270 (°)	113
UGRL	20
Efficiency (lm/W)	38.22



Beam Angle: 113°

h(m)	E(lx)	D(m)
1	534	3.02
2	134	6.04
3	59	9.06
4	33	12.08
5	21	15.10

Luminous flux luminaire
1529 lm

Electrical

Voltage (V)	48	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable		
	Casambi		
Emergency	Without		

Physical

Color	White/White
Orientation	Fixed
Weight (kg)	5.16
Length (mm)	605
Lifespan (L70 B10)	L80B50

Note

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

