


## Suspension Panel 600 Rod 400 mm Casambi integrated

New

03.8143.40.CB - White/White

Suspended luminaire with rigid rod, to be installed in the Infra-Structure system.




### Main specifications

|                  |       |                |                     |
|------------------|-------|----------------|---------------------|
| Number of heads  | 1     | CRI            | 90                  |
| Lamp category    | LED   | Net lumen (lm) | 1618                |
| Power (W)        | 40W   | Mountings      | Track               |
| System power (W) | 40    | Environment    | Indoor dry location |
| CCT (K)          | 3000K |                |                     |

### Optical

|                        |                |
|------------------------|----------------|
| Lighting type          | Direct         |
| LED type               | Top LED        |
| Light distribution     | Symmetric      |
| Optical type           | Diffused light |
| Beam angle (°)         | 113            |
| Beam angle C90-270 (°) | 113            |
| UGRL                   | 20             |
| Efficiency (lm/W)      | 40.45          |



Beam Angle: 113°

| h(m) | E(lx) | D(m)  |
|------|-------|-------|
| 1    | 565   | 3.02  |
| 2    | 141   | 6.04  |
| 3    | 63    | 9.06  |
| 4    | 35    | 12.08 |
| 5    | 23    | 15.10 |

Luminous flux luminaire  
1618 lm

### Electrical

|             |                 |                  |     |
|-------------|-----------------|------------------|-----|
| Voltage (V) | 48              | Insulation class | III |
| Dimmable    | Yes             |                  |     |
| Driver      | Remote excluded |                  |     |
| Driver type | Dimmable        |                  |     |
|             | Casambi         |                  |     |
| Emergency   | Without         |                  |     |

### Physical

|                    |             |
|--------------------|-------------|
| Color              | White/White |
| Orientation        | Fixed       |
| Weight (kg)        | 5.16        |
| Length (mm)        | 605         |
| Lifespan (L70 B10) | L80B50      |

### Note

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

