


## Suspension Panel 600 Rod 400 mm Dali Version

■ 03.8141.14.DA - Black/Gold

Suspended luminaire with rigid rod, to be installed in the Infra-Structure system.




### Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	1486
Power (W)	40W	Mountings	Track
System power (W)	40	Environment	Indoor dry location
CCT (K)	2700K		

### Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	114
Beam angle C90-270 (°)	114
UGRL	20
Efficiency (lm/W)	37.15



Beam Angle: 114°

h(m)	E(lx)	D(m)
1	516	3.06
2	129	6.11
3	57	9.17
4	32	12.22
5	21	15.28

Luminous flux luminaire  
1486 lm

### Electrical

Voltage (V)	48	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable DALI		
	1		
Emergency	Without		

### Physical

Color	Black/Gold
Orientation	Fixed
Weight (kg)	5.16
Length (mm)	605
Lifespan (L70 B10)	L80B50

### Note

Only compatible with DALI profile version.

