

## Suspension Panel 600 Rod 400 mm Dali Version

03.8143.40.DA - White/White

Suspended luminaire with rigid rod, to be installed in the Infra-Structure system.




### Main specifications

|                        |       |                       |        |
|------------------------|-------|-----------------------|--------|
| <b>Number of heads</b> | 1     | <b>Net lumen (lm)</b> | 1618   |
| <b>Lamp category</b>   | LED   | <b>Mountings</b>      | Track  |
| <b>Power (W)</b>       | 40W   | <b>Environment</b>    | Indoor |
| <b>CCT (K)</b>         | 3000K |                       |        |
| <b>CRI</b>             | 90    |                       |        |

### Optical


|                               |                |
|-------------------------------|----------------|
| <b>Lighting type</b>          | Direct         |
| <b>LED type</b>               | Top LED        |
| <b>Light distribution</b>     | Symmetric      |
| <b>Optical type</b>           | Diffused light |
| <b>Beam angle (°)</b>         | 113            |
| <b>Beam angle C90-270 (°)</b> | 113            |



Beam Angle: 113°

| h(m) | E(lx) | D(m)  |
|------|-------|-------|
| 1    | 565   | 3.02  |
| 2    | 141   | 6.04  |
| 3    | 63    | 9.06  |
| 4    | 35    | 12.08 |
| 5    | 23    | 15.10 |

Luminous flux luminaire  
1618 lm



### Electrical

|                    |                          |                         |     |
|--------------------|--------------------------|-------------------------|-----|
| <b>Voltage (V)</b> | 48.00                    | <b>Insulation class</b> | III |
| <b>Dimmable</b>    | Yes                      |                         |     |
| <b>Driver</b>      | Remote                   |                         |     |
| <b>Driver type</b> | Electronic dimmable DALI |                         |     |
| <b>Emergency</b>   | Without                  |                         |     |

### Physical

|                    |             |
|--------------------|-------------|
| <b>Color</b>       | White/White |
| <b>Orientation</b> | Fixed       |
| <b>Weight (kg)</b> | 5.16        |
| <b>Length (mm)</b> | 605         |

### Note

Only compatible with DALI profile version.

