




03.0051.14ANT - Black


Recessed integrated luminaire with 2 LED lighting spots. 1050 mA remote power supply not included.











Main specifications


Number of heads 2 LED Lamp category Power (W) 6.5W CCT (K) 2700K CRI 90

Net lumen (lm) Mountings Environment

Ceiling recessed Indoor dry location

Optical

Lighting type Direct LED type Power LED Light distribution Symmetric Optical type Spot Beam angle (°) 11 Beam angle C90-270 (°) 12



Luminous flux luminaire 341 lm (EXTREME CUT OFF)

Beam Angle:		12°
h(m)	E(lx)	D(m)
1	6324	0.20
2	1581	0.40
3	703	0.60
4	395	0.80

253

1.00

5

Electrical

Dimmable No Remote Driver excludedDriver type Non Dimmable Emergency Without Insulation class

Physical

Color Black Orientation Fixed Recessed depth (mm) 100 Weight (kg) 0.74 Length (mm) 190

Note

No Trim version can be connected in a continuous line.

The Black Line No Trim 2 Spots



Continuous current power supply of 25-50W, 110/240V – 50/60Hz with power current selected through adjustable 350mA – 25W /500mA – 35W/ 700mA – 50W /750mA – 54W /900/ 1050 mA – 60W switch. Dali 2, 0/1-10V or push dimming 60.8530