



## The Black Line No Trim 4 Spots

■ 03.0056.14ANT - Black

Recessed integrated luminaire with 4 LED lighting spots. 1050 mA remote power supply not included.




### Main specifications

<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	13W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		
<b>Net lumen (lm)</b>	713		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	42
<b>Beam angle C90-270 (°)</b>	44



<b>Beam Angle:</b>	44°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	1475	0.77	
2	369	1.54	
3	164	2.31	
4	92	3.08	
5	59	3.85	

Luminous flux luminaire  
713 lm (EXTREME CUT OFF)

### Electrical

<b>Dimmable</b>	No
<b>Driver</b>	Remote excluded
<b>Driver type</b>	Non Dimmable
<b>Emergency</b>	Without
<b>Insulation class</b>	III

### Physical

<b>Color</b>	Black
<b>Orientation</b>	Fixed
<b>Recessed depth (mm)</b>	100
<b>Weight (kg)</b>	1.27
<b>Length (mm)</b>	350

### Note

No Trim version can be connected in a continuous line.

## The Black Line No Trim 4 Spots



---

Constant Current Power Supply for  
LED. 24/33W  
60.8548

---

Continuous current power supply of  
20-40W, 110/240V – 50/60Hz. Power  
current selected through adjustable  
350mA-18,5W / 400mA-21W / 500mA-  
26,5W / 600mA-31,5W / 650mA-34,5W /  
700mA-37W / 750mA-39,5W /  
800/850/900/950/1000/1050/1200 mA-  
40W switch  
60.9276