Ceiling recessed

Indoor dry location





03.0057.14ANT - Black

Recessed integrated luminaire with 4 LED lighting spots. 1050 mA remote power supply not included.


Mountings


Environment












•	
Lamp category	LED
Power (W)	13W
CCT (K)	2700K
CRI	90
Net lumen (lm)	626

Main specifications

Optical

Lighting type Direct LED type Power LED Light distribution Symmetric Optical type Beam angle (°) Flood 42 Beam angle C90-270 (°) 44



k /		1	
Lumino	ous fl	ux lur	ninaire
626 lm	(FXT	REME C	UT OFF)

Bean	Beam Angle:	
h(m)	E(lx)	D(m)
1	1296	0.77
2	324	1.54
3	144	2.31
4	81	3.08

52

3.85

Electrical

Dimmable No Driver Remote excludedDriver type Non Dimmable Emergency Without Insulation class

Physical

Color Black Orientation Fixed Recessed depth (mm) 100 Weight (kg) 1.27 Length (mm) 350

Note

No Trim version can be connected in a continuous line.

The Black Line No Trim 4 Spots





Constant Current Power Supply for LED. 24/33W 60.8548 Continuous current power supply of 20-40W, 110/240V – 50/60Hz. Power current selected through adjustable 350mA-18,5W / 400mA-21W / 500mA-26,5W / 600mA-31,5W / 650mA-34,5W / 700mA-37W / 750mA-39,5W / 800/850/900/950/1000/1050/1200 mA-40W switch 60.9276