




03.0058.14ANT - Black


Recessed integrated luminaire with 8 LED lighting spots. 1050 mA remote power supply not included.












•	
Lamp category	LED
Power (W)	26W
CCT (K)	3000K
CRI	90
Net lumen (lm)	1553

Main specifications

Ceiling recessed Mountings Environment Indoor dry location

Optical

Lighting type Direct LED type Power LED Light distribution Symmetric Optical type Spot Beam angle (°) 11 Beam angle C90-270 (°) 12



Luminous flux luminaire 1553 lm (EXTREME CUT OFF)

Bea	am Angle	: 12°
h(m) E(lx)	D(m)
1_	28800	0.20
2	7200	0.40
3	3200	0.60

1800

1152

0.80

1.00

Electrical

Dimmable No Remote Driver excludedDriver type Non Dimmable Emergency Without

Physical

Insulation class

Color Black Orientation Fixed Recessed depth (mm) 100 Weight (kg) 2.34 Length (mm) 670

Note

No Trim version can be connected in a continuous line.

The Black Line No Trim 8 Spots





Continuous current power supply of 20-40W, 110/240V – 50/60Hz. Power current selected through adjustable 350mA-18,5W / 400mA-21W / 500mA-26,5W / 600mA-31,5W / 650mA-34,5W / 700mA-37W / 750mA-39,5W / 800/850/900/950/1000/1050/1200 mA-40W switch 60.9276

Constant Current Power Supply for LED. 24/33W 60.8548