





03.0064.40A - White

Recessed integrated luminaire with 12 LED lighting spots. 1050 mA remote power supply not included.









Main specifications	
Lamp category	LED
Power (W)	39W

 CCT (K)
 3000K


 CRI
 90

 Net lumen (lm)
 2139

Mountings Environment Ceiling recessed Indoor dry location

Optical

Lighting type Direct
LED type Power LED
Light distribution Symmetric
Optical type Flood
Beam angle (°) 42
Beam angle C90-270 (°) 44



Luminous flux luminaire 2139 lm (EXTREME CUT OFF)

Beam Angle:		44°
h(m)	E(lx)	D(m)
1	4425	0.77
2	1106	1.54
3	492	2.31
4	277	3.08

177

3.85

5

Electrical

Frequency (Hz) 50/60 Insulation class III
Dimmable No
Driver Remote

Driver type excluded Non Dimmable Emergency Without

Physical

 Color
 White

 Orientation
 Fixed

 Recessed depth (mm)
 105

 Weight (kg)
 3.81

 Length (mm)
 1031

The Black Line Trim 12 Spots



Continuous current power supply of 25-50W, 110/240V – 50/60Hz with power current selected through adjustable 350mA – 25W /500mA – 35W/ 700mA – 50W /750mA – 54W /900/ 1050 mA – 60W switch. Dali 2, 0/1-10V or push dimming 60.8530