

The Black Line Trim 2 Spots

03.0052.40A - White

Recessed integrated luminaire with 2 LED lighting spots. 1050 mA remote power supply not included.




Main specifications

Lamp category	LED	Mountings	Ceiling recessed
Power (W)	6.5W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		
Net lumen (lm)	356		


Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	42
Beam angle C90-270 (°)	44



Beam Angle:	44°		
h(m)	E(lx)	D(m)	
1	738	0.77	
2	184	1.54	
3	82	2.31	
4	46	3.08	
5	30	3.85	

Luminous flux luminaire
356 lm (EXTREME CUT OFF)




Electrical

Frequency (Hz)	50/60	Insulation class	III
Dimmable	No		
Driver	Remote excluded		
Driver type	Non Dimmable		
Emergency	Without		

Physical

Color	White
Orientation	Fixed
Recessed depth (mm)	105
Weight (kg)	0.84
Length (mm)	231



The Black Line Trim 2 Spots



Continuous current power supply of
25-50W, 110/240V – 50/60Hz with power
current selected through adjustable
350mA – 25W /500mA – 35W/ 700mA –
50W /750mA – 54W /900/ 1050 mA –
60W switch. Dali 2, 0/1-10V or push
dimming
60.8530