





03.0055.40A - White

Recessed integrated luminaire with 4 LED lighting spots. 1050 mA remote power supply not included.










Main specifications

_amp category	LED
Power (W)	13W
CCT (K)	2700K
CRI	90
Net lumen (lm)	682

Mountings Environment Ceiling recessed Indoor dry location

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	11
Beam angle C90-270 (°)	12



Luminous flux luminaire 682 lm (EXTREME CUT OFF)

Beam Ang l e:		12°
h(n	n) E(l x)	D(m)
1_	12649	0.20
2	3162	0.40
3	1405	0.60
4	791	0.80
5	506	1 00

Electrical

Frequency (Hz)	50/60	Insulation class	Ш
Dimmable	No		
Driver	Remote		
	1 1 1		

Driver type excluded Non Dimmable Emergency Without

Physical

Color	Whit
Orientation	Fixed
Recessed depth (mm)	105
Weight (kg)	1.47
Length (mm)	391

The Black Line Trim 4 Spots





Continuous current power supply of 20-40W, 110/240V – 50/60Hz. Power current selected through adjustable 350mA-18,5W / 400mA-21W / 500mA-26,5W / 600mA-31,5W / 650mA-34,5W / 700mA-37W / 750mA-39,5W / 800/850/900/950/1000/1050/1200 mA-40W switch 60.9276

Constant Current Power Supply for LED. 24/33W 60.8548