


## The Black Line Trim 8 Spots

03.0061.00A - Primer

Recessed integrated luminaire with 8 LED lighting spots. 1050 mA remote power supply not included.




### Main specifications

<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	26W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		
<b>Net lumen (lm)</b>	1253		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	42
<b>Beam angle C90-270 (°)</b>	44



<b>Beam Angle:</b>	44°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	2591	0.77	
2	648	1.54	
3	288	2.31	
4	162	3.08	
5	104	3.85	

Luminous flux luminaire  
1253 lm (EXTREME CUT OFF)


### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	III
<b>Dimmable</b>	No		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Primer
<b>Orientation</b>	Fixed
<b>Recessed depth (mm)</b>	105
<b>Weight (kg)</b>	2.54
<b>Length (mm)</b>	711

### Certification / Marking



## The Black Line Trim 8 Spots



---

Continuous current power supply of 20-40W, 110/240V – 50/60Hz with power current selected through adjustable switch. Synchronisation cables not included.  
60.9276

---

Constant Current Power Supply for LED. 24/33W  
60.8548