



## The Fast Track Spot 100

■ 09.9016.14 - Black


Spotlight to be installed in the The Fast Track system profile with a LED light source and super spot optic, very useful for great heights, medium and flood.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	600
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	13W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	4000K		
<b>CRI</b>	90		


### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	15
<b>Beam angle C90-270 (°)</b>	15



<b>Beam Angle:</b>	15°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	6339	0.26	
2	1585	0.52	
3	704	0.77	
4	396	1.03	
5	254	1.29	

Luminous flux luminaire  
600 lm



### Electrical

<b>Voltage (V)</b>	48.00	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote excluded		
<b>Driver type</b>	Non Dimmable		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Black	<b>Spot diameter (mm)</b>	105
<b>Orientation</b>	Adjustable	<b>Length (mm)</b>	180
<b>Weight (kg)</b>	1		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		

### Note

The boxes of the luminaries are manufactured only in black.

