



## The Fast Track Spot 100 Casambi integrated

New

■ 09.9075.14 - Black

Spotlight to be installed in the The Fast Track system profile with a LED light source and super spot optic, very useful for great heights, medium and flood.


### Main specifications

Number of heads	1	Net lumen (lm)	667
Lamp category	LED	Mountings	Track
Power (W)	13W	Environment	Indoor
CCT (K)	4000K		
CRI	90		




### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Super spot
Beam angle (°)	4
Beam angle C90-270 (°)	4



Beam Angle:	4°		
	h(m)	E(lx)	D(m)
1	68792	0.07	
2	17198	0.14	
3	7644	0.21	
4	4300	0.28	
5	2752	0.35	

Luminous flux luminaire  
667 lm



### Electrical

Voltage (V)	48.00	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic dimmable		
Emergency	Without		

### Physical

Color	Black	Spot diameter (mm)	105
Orientation	Adjustable	Length (mm)	180
Weight (kg)	1		
Tilt (°)	90		
Rotation (°)	360		

### Note

The boxes of the luminaries are manufactured only in black. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

