



The Fast Track Spot 100 Casambi integrated

New

09.9076.BW - White

Spotlight to be installed in the The Fast Track system profile with a LED light source and super spot optic, very useful for great heights, medium and flood.


Main specifications

| | | | |
|-----------------|-------|----------------|--------|
| Number of heads | 1 | Net lumen (lm) | 600 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 13W | Environment | Indoor |
| CCT (K) | 4000K | | |
| CRI | 90 | | |




Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 15 |
| Beam angle C90-270 (°) | 15 |



| | |
|-------------|------------|
| Beam Angle: | 15° |
| h(m) | E(lx) D(m) |
| 1 | 6339 0.26 |
| 2 | 1585 0.52 |
| 3 | 704 0.77 |
| 4 | 396 1.03 |
| 5 | 254 1.29 |

Luminous flux luminaire
600 lm



Electrical

| | | | |
|-------------|---------------------|------------------|-----|
| Voltage (V) | 48.00 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote | | |
| Driver type | Electronic dimmable | | |
| Emergency | Without | | |

Physical

| | | | |
|--------------|------------|--------------------|-----|
| Color | White | Spot diameter (mm) | 105 |
| Orientation | Adjustable | Length (mm) | 180 |
| Weight (kg) | 1 | | |
| Tilt (°) | 90 | | |
| Rotation (°) | 360 | | |

Note

The boxes of the luminaries are manufactured only in black. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

