



## The Fast Track Spot 150 Casambi integrated

New

09.9083.BW - White

Spotlight to be installed in the The Fast Track system profile with a LED light source and glass optics: high performance spot, medium and flood lights.


### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1872
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	25.5W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		




### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	16
<b>Beam angle C90-270 (°)</b>	16



<b>Beam Angle:</b>	16°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	17329	0.28	
2	4332	0.56	
3	1925	0.84	
4	1083	1.12	
5	693	1.40	

Luminous flux luminaire  
1872 lm



### Electrical

<b>Voltage (V)</b>	48.00	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote excluded		
<b>Driver type</b>	Dimmable		
<b>Emergency</b>	Casambi		
	Without		

### Physical

<b>Color</b>	White	<b>Spot diameter (mm)</b>	57
<b>Orientation</b>	Adjustable	<b>Length (mm)</b>	240
<b>Weight (kg)</b>	0.83		
<b>Tilt (°)</b>	90		
<b>Rotation (°)</b>	360		

### Note

The boxes of the luminaires are manufactured only in black. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi. Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.



## The Fast Track Spot 150 Casambi integrated



---

Flood lens  
08.8432.00



---

Honeycomb  
08.8428.00



---

Screening crosspiece  
08.8429.00



---

Snoot shielding cone  
08.0526.BW




---

Snoot shielding cone  
08.0526.40



---

Snoot shielding cone  
08.0526.00



---

Elliptical lens  
08.8431.00