



The Fast Track Spot 150 Casambi integrated

■ 09.9085.14 - Black


Spotlight to be installed in the The Fast Track system profile with a LED light source and glass optics: high performance spot, medium and flood lights.

Main specifications

| | | | |
|------------------------|-------|-----------------------|--------|
| Number of heads | 1 | Net lumen (lm) | 1838 |
| Lamp category | LED | Mountings | Track |
| Power (W) | 25.5 | Environment | Indoor |
| CCT (K) | 3000K | | |
| CRI | 90 | | |


Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 40 |
| Beam angle C90-270 (°) | 40 |



| | | | |
|-------------|------|-------|------|
| Beam Angle: | 40° | | |
| | h(m) | E(lx) | D(m) |
| 1 | 4656 | 0.73 | |
| 2 | 1164 | 1.46 | |
| 3 | 517 | 2.18 | |
| 4 | 291 | 2.91 | |
| 5 | 186 | 3.64 | |

Luminous flux luminaire
1838 lm



Electrical


| | | | |
|--------------------|---------------------|-------------------------|-----|
| Voltage (V) | 48.00 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote | | |
| Driver type | Electronic dimmable | | |
| Emergency | Without | | |

Physical

| | | | |
|---------------------|------------|---------------------------|-----|
| Color | Black | Spot diameter (mm) | 57 |
| Orientation | Adjustable | Length (mm) | 240 |
| Weight (kg) | 0.83 | | |
| Tilt (°) | 90 | | |
| Rotation (°) | 360 | | |

Note

The boxes of the luminaires are manufactured only in black. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi. Screening crosspiece, lenses and honeycomb directly installable on the head of the luminaire without needing any fastening accessory. Installation compatible with honeycomb + lense at the same time.



The Fast Track Spot 150 Casambi integrated



Snoot shielding cone
08.0526.40



Snoot shielding cone
08.0526.00



Snoot shielding cone
08.0526.BW



Honeycomb
08.8428.00



Flood lens
08.8432.00



Elliptical lens
08.8431.00



Screening crosspiece
08.8429.00