



The Fast Track Spot 175 Casambi integrated

New

09.9095.BW - White


Spotlight to be installed in the The Fast Track system profile with a LED light source and glass optics: high performance spot, medium and flood lights.

Main specifications

Number of heads	1	Net lumen (lm)	2903
Lamp category	LED	Mountings	Track
Power (W)	38.5W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	35
Beam angle C90-270 (°)	35



Beam Angle: 35°

h(m)	E(lx)	D(m)
1	8173	0.64
2	2043	1.28
3	908	1.92
4	511	2.55
5	327	3.19

Luminous flux luminaire
2903 lm

Electrical

Voltage (V)	48.00	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic dimmable		
Emergency	Without		

Physical

Color	White	Spot diameter (mm)	75
Orientation	Adjustable	Length (mm)	240
Weight (kg)	1.18		
Tilt (°)	90		
Rotation (°)	360		

Note

The boxes of the luminaires are manufactured only in black. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

