



## The Fast Track Spot 175 Casambi integrated

New

■ 09.9096.14 - Black

Spotlight to be installed in the The Fast Track system profile with a LED light source and glass optics: high performance spot, medium and flood lights.


### Main specifications

Number of heads	1	Net lumen (lm)	3178
Lamp category	LED	Mountings	Track
Power (W)	38.5W	Environment	Indoor
CCT (K)	4000K		
CRI	90		




### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	12
Beam angle C90-270 (°)	12



Beam Angle:	12°		
	h(m)	E(lx)	D(m)
1	32771	0.22	
2	8193	0.43	
3	3641	0.65	
4	2048	0.87	
5	1311	1.08	

Luminous flux luminaire  
3178 lm



### Electrical

Voltage (V)	48.00	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic dimmable		
Emergency	Without		

### Physical

Color	Black	Spot diameter (mm)	75
Orientation	Adjustable	Length (mm)	240
Weight (kg)	1.18		
Tilt (°)	90		
Rotation (°)	360		

### Note

The boxes of the luminaires are manufactured only in black. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

