



The Micro Running Magnet Recessed Profile

New

06.6001.14 - Black

Electromechanical profile of reduced size for recessed installation in plasterboard ceilings/walls with lengths from 1 to 3 m.



Main specifications

Power (W)	MAX 120W
Mountings	Recessed
Environment	Indoor dry location

Electrical

Dimmable	Yes
Driver	Remote excluded
Driver type	Non Dimmable, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1
Emergency	Without

Physical

Color	Black
Length (mm)	1500

Note

Fastening accessories included with the profiles. 90° corners available in the same plane (symmetrical element for left and right corners).

PWM voltage output dimmable drivers shall be used at frequencies between 250 and 500Hz.



The Micro Running Magnet Recessed Profile



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 25W 110/240V
60.9359



24V Remote power supply. Dimmable through 1/10V protocol. 120W 110/240V
60.9681



24V Remote power supply. Dimmable through DALI protocol. 120W 110/240V
60.9682




24V Remote power supply. Dimmable through CASAMBI protocol. 120W 110/240V
60.9683



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. Dimming range 20-100%. 36W-110V / 45W-240V
60.9360



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 57W 220/240V
60.9361



Casambi Controller 220-240V. Remote Installation
60.9362

