



The Micro Running Magnet Surface Profile

New

06.6014.40 - White

Electromechanical profile of reduced size for installation on surfaces with lengths from 1 to 3 m.

Main specifications

Power (W)	MAX 120W
Mountings	Surface
Environment	Indoor dry location

Electrical

Voltage (V)	24	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1		
Emergency	Without		

Physical

Color	White
Weight (kg)	0.49
Length (mm)	3000

Note

Fastening accessories included with the profiles. 90° corners available in the same plane (symmetrical element for left and right corners). The inner part of the profile is always supplied in black.
PWM voltage output dimmable drivers shall be used at frequencies between 250 and 500Hz.

The Micro Running Magnet Surface Profile



Recessed/Surface End Caps. 1 unit kit
06.6036.40



Casambi Controller 220-240V. Remote Installation
60.9392



24V Remote power supply. Dimmable through 1/10V protocol. 120W 110/240V
60.9681



Recessed/Surface Feed Connector
06.6034.40



24V Remote power supply. Dimmable through CASAMBI protocol. 120W 110/240V
60.9683



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 25W 110/240V
60.9359



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. Dimming range 20-100%. 36W-110V / 45W-240V
60.9360



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 57W 220/240V
60.9361



24V Remote power supply. Dimmable through DALI protocol. 120W 110/240V
60.9682

