

## The Running Magnet Suspension Up&Down Intermediate Profile

### 06.1622.14A - Black

Electromechanical track for suspended installations. Linear elements in the Up&Down version include indirect LED illumination in the upper part of the profile. Shared or separate power feed. Linear profiles available in two versions: power feed profiles for connecting to a driver, and intermediate profiles.


Electromechanical track for suspended installations. Linear elements in the Up&Down version include indirect LED illumination in the upper part of the profile. Shared or separate power feed. Linear profiles available in two versions: power feed profiles for connecting to a driver, and intermediate profiles.

### Main specifications

<b>Lamp category</b>	LED	<b>Net lumen (lm)</b>	2109
<b>Power (W)</b>	21W	<b>Mountings</b>	Suspension
<b>System power (W)</b>	22.1	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Indirect
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Beam angle (°)</b>	98
<b>Beam angle C90-270 (°)</b>	91
<b>Efficiency (lm/W)</b>	95.43



Beam Angle: 91°

h(m)	E(lx)	D(m)
1	910	2.05
2	227	4.10
3	101	6.15
4	57	8.20
5	36	10.25

Luminous flux luminaire  
2109 lm

### Electrical

<b>Voltage (V)</b>	24.00
<b>Emergency</b>	Without
<b>Insulation class</b>	III

### Physical

<b>Color</b>	Black
<b>Weight (kg)</b>	6.00
<b>Length (mm)</b>	2500
<b>Lifespan (L70 B10)</b>	L80B50

### Note

Covers included with the power feed profiles. Ceiling connection (4.2 m feed cable) and suspension (4m steel cable) accessories included in all linear feed or intermediate products.

90° corners in the same plane (symmetrical element for right and left corners). Not provided for connection to the driver.

The corners of the Suspended Running Magnet versions are not fitted with indirect illumination. Indirect illumination can be managed as a separate circuit if powered by a dedicated driver and, in the case of the DALI installation, if equipped with a dedicated optional DALI controller.

To be ordered separately.

Profiles cannot be cut.

The inner part of the profile is always supplied in black.

## The Running Magnet Suspension Up&Down Intermediate Profile



---

Endcap. 2 unit kit  
08.8887.14A