

The Tracking Magnet Surface Profile Inner Mechanical Corner

06.5016.05 - Polished Aluminium

Electromechanical profile for surface-mounting, available in lengths from 1m to 3m.



Main specifications

Mountings	Surface
Environment	Indoor dry location

Electrical


Voltage (V)	48.00
Emergency	Without

Physical

Color	Polished Aluminium
Weight (kg)	0.20
Length (mm)	55

Note

Inner mechanical corner. Only for surface version.



The Tracking Magnet Surface Profile Inner Mechanical Corner



Surface rose
08.8883.40A



1 m suspension rod with ceiling rose
with m6 thread
60.3097.14



1 m suspension rod with ceiling rose
with m6 thread
60.3097.11



The Tracking Magnet
Surface/Suspension Profile End Caps
06.5017.05




4-pole, 0.75 mm² section, 4-meter long,
transparent power cable
06.0157.00



4m suspension steel cable
08.8634.00



Ceiling fixing kit
08.0615.00



Surface rose
08.8883.14A



Ceiling fixing kit
08.0616.00



Recessed power supply rose
08.8889.40



Suspension rod with 1m rose. M6
thread
60.3014.14



Recessed power supply rose
08.8889.14



Suspension rod with 1m rose. M6
thread
60.3014.11



The Tracking Magnet Profile
Intermediate Connector
Flexible/Electrical Corner
08.0614.14