



Theblockoflight

■ 09.3310.72C - Grey


Semi-recessed signalling lamp for indoor or outdoor use. Non-regulable 100-240V, 50-60Hz power supply and 500 mm power cable included.

Main specifications

| | | | |
|-----------------------|-------|--------------------|---|
| Lamp category | LED | Mountings | Wall recessed |
| Power (W) | 2.2W | Environment | Indoor dry location, Outdoor wet location |
| CCT (K) | 3000K | | |
| CRI | 80 | | |
| Net lumen (lm) | 50 | | |

Optical


| | |
|-------------------------------|------------------|
| Lighting type | Indirect, Direct |
| LED type | Power LED |
| Light distribution | Asymmetric |
| Beam angle (°) | 45 |
| Beam angle C90-270 (°) | 58 |



Beam Angle: 45°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 6 | 1.85 |
| 2 | 2 | 3.70 |
| 3 | 1 | 5.55 |
| 4 | 0 | 7.40 |
| 5 | 0 | 9.25 |

Luminous flux luminaire
50 lm




Electrical

| | | | |
|-----------------------|--------------|-------------------------|---|
| Frequency (Hz) | 50/60 | Insulation class | I |
| Dimmable | No | | |
| Driver | Integrated | | |
| Driver type | Non Dimmable | | |
| Emergency | Without | | |

Physical

| | |
|----------------------------|-------|
| Color | Grey |
| Orientation | Fixed |
| Recessed depth (mm) | 47 |
| Weight (kg) | 0.4 |
| Length (mm) | 75 |



Theblockoflight



Can for embedding in concrete.

08.8423.00