



## Thin LED 404 mm

■ 09.0045.BZB - Anodized Bronze

Wall application luminaire for indirect lighting with LED. Remote transformer not included.




### Main specifications

|                        |       |                       |                     |
|------------------------|-------|-----------------------|---------------------|
| <b>Number of heads</b> | 1     | <b>Net lumen (lm)</b> | 621                 |
| <b>Lamp category</b>   | LED   | <b>Mountings</b>      | Wall surface        |
| <b>Power (W)</b>       | 6.8W  | <b>Environment</b>    | Indoor dry location |
| <b>CCT (K)</b>         | 3000K |                       |                     |
| <b>CRI</b>             | 90    |                       |                     |

### Optical

|                               |                |
|-------------------------------|----------------|
| <b>Lighting type</b>          | Indirect       |
| <b>LED type</b>               | Top LED        |
| <b>Light distribution</b>     | Asymmetric     |
| <b>Optical type</b>           | Diffused light |
| <b>Beam angle (°)</b>         | 101            |
| <b>Beam angle C90-270 (°)</b> | 43             |



Beam Angle: 43°

| h(m) | E(lx) | D(m)  |
|------|-------|-------|
| 1    | 118   | 6.46  |
| 2    | 30    | 12.92 |
| 3    | 13    | 19.38 |
| 4    | 7     | 25.84 |
| 5    | 5     | 32.30 |

Luminous flux luminaire  
621 lm

### Electrical


|                    |   |                         |     |
|--------------------|---|-------------------------|-----|
| <b>Voltage (V)</b> | 24.00   | <b>Insulation class</b> | III |
| <b>Dimmable</b>    | No  |                         |     |
| <b>Driver</b>      | Remote excluded                               |                         |     |
| <b>Driver type</b> | Non Dimmable, Dimmable 1-10V, Dimmable DALI 1 |                         |     |
| <b>Emergency</b>   | Without                                       |                         |     |

### Physical

|                    |                 |
|--------------------|-----------------|
| <b>Color</b>       | Anodized Bronze |
| <b>Orientation</b> | Fixed           |
| <b>Weight (kg)</b> | 0.30            |
| <b>Length (mm)</b> | 404             |

### Note

16 LEDs



## Thin LED 404 mm



---

Electronic transformer with constant voltage (24V) for LED. 100/240V. 25W  
60.8703



---

Dimmable 1-10V control unit with 1 channel for 24V LED modules. Max. 120W - 5A  
60.8640



---

Electronic transformer with constant voltage (24V) for LED. 100/240V. 60W  
60.9089



---

Electronic transformer with constant voltage (24V) for LED. 100/240V. 120W  
60.9407



---

Dimmable DALI control unit with 1 channel for 24V LED modules. Power supply not included  
60.8635