









Three Phase Track Recessed Dali 2000 mm

60.3820.11ADA - Matt White

GLOBALTRACK offers benefits for advanced installations: the main connectors are feedable and the feeding cable can be hidden under the elegantsuspension accessories. GLOBALTRACK lighting tracks are designed for easy surface mounting on ceilings and walls, or recessed mounting insuspended ceilings. Lighting tracks can be suspended at any desired height.

Main specifications

Mountings Ceiling recessed
Environment Indoor dry
location

Electrical

Emergency Without Insulation class

Physical

 Color
 Matt White

 Weight (kg)
 0.80

 Length (mm)
 2000

Three Phase Track Recessed Dali 2000 mm







Straight Connector Dali 60.3044.11ADA

Cross Coupling Dali 60.3036.14ADA Connector 90° Inside Dali 60.3029.11ADA







Connector 90° Outside Dali 60.3028.11ADA

Fix-point 60.3023.14

Connector 90° Inside Dali 60.3029.14ADA







Cover for connectors DALI 60.3146.11

Straight Connector Dali 60.3044.12ADA

Connector T – Inside Left Dali 60.3048.29ADA







Connector 90° Inside Dali 60.3029.29ADA

Blind end 60.3016.12

Mean connector Dali 60.3043.14ADA







Cover for connectors DALI 60.3146.14

Fix-point 60.3023.11

Cross Coupling Dali 60.3036.29ADA







Connector 90° Outside Dali 60.3028.29ADA

Recessed box for fix-point 60.3022.11

Fix-point 60.3023.29







Connector 90° Outside Dali 60.3028.14ADA	Connector T – Inside Right Dali 60.3047.14ADA	Blind end 60.3016.11
Cover for power supply connectors recessed track 60.3053.11	Cross Coupling Dali 60.3036.11ADA	Blind end 60.3016.14
	CIOBALISANIAN	
Mean connector Dali 60.3043.29ADA	Lead bending key 60.3054	Straight Connector Dali 60.3044.14ADA
Connector T – Inside Left Dali 60.3048.11ADA	Mean connector Dali 60.3043.11ADA	Connector T – Inside Left Dali 60.3048.14ADA







Connector T – Inside Right Dali 60.3047.11ADA Connector T – Inside Right Dali 60.3047.29ADA

Cover for power supply connectors recessed track 60.3053.14



Recessed box for fix-point 60.3022.14