


Three Phase Track Recessed Dali 3000 mm

60.3830.29ADA - Aluminum

GLOBALTRACK offers benefits for advanced installations: the main connectors are feedable and the feeding cable can be hidden under the elegant suspension accessories. GLOBALTRACK lighting tracks are designed for easy surface mounting on ceilings and walls, or recessed mounting in suspended ceilings. Lighting tracks can be suspended at any desired height.



Main specifications

Mountings	Ceiling recessed
Environment	Indoor dry location

Electrical

Emergency	Without
Insulation class	I

Physical

Color	Aluminum
Weight (kg)	0.80
Length (mm)	3000



Three Phase Track Recessed Dali 3000 mm



Straight Connector Dali
60.3044.14ADA



Connector T – Inside Left Dali
60.3048.29ADA



Mean connector Dali
60.3043.14ADA



Connector 90° Outside Dali
60.3028.29ADA



Cover for connectors DALI
60.3146.11



Cross Coupling Dali
60.3036.11ADA



Cover for connectors DALI
60.3146.14



Straight Connector Dali
60.3044.11ADA



Blind end
60.3016.12



Lead bending key
60.3054



Blind end
60.3016.11



Fix-point
60.3023.14



Straight Connector Dali
60.3044.12ADA



Connector 90° Inside Dali
60.3029.14ADA



Fix-point
60.3023.11



Connector T – Inside Right Dali
60.3047.11ADA



Connector 90° Outside Dali
60.3028.14ADA



Cross Coupling Dali
60.3036.29ADA





Cover for power supply connectors
recessed track

60.3053.11



Fix-point
60.3023.29

Connector T – Inside Right Dali
60.3047.14ADA

Connector 90° Inside Dali
60.3029.11ADA



Recessed box for fix-point
60.3022.14

Blind end
60.3016.14

Connector 90° Inside Dali
60.3029.29ADA



Cover for power supply connectors
recessed track

Connector 90° Outside Dali
60.3028.11ADA

Mean connector Dali
60.3043.11ADA



Connector T – Inside Left Dali
60.3048.11ADA



Connector T – Inside Right Dali
60.3047.29ADA



Cross Coupling Dali
60.3036.14ADA



Recessed box for fix-point
60.3022.11