

Three Phase Track Surface/Pendant 2000 mm

■ 60.3102.14 - Matt Black

GLOBALTRACK offers benefits for advanced installations: the main connectors are feedable and the feeding cable can be hidden under the elegant suspension accessories. GLOBALTRACK lighting tracks are designed for easy surface mounting on ceilings and walls, or recessed mounting in suspended ceilings. Lighting tracks can be suspended at any desired height.

Main specifications




Mountings	Surface and suspension
Environment	Indoor dry location

Electrical

Emergency	Without
Insulation class	I

Physical

Color	Matt Black
Weight (kg)	1.60
Length (mm)	2000



Three Phase Track Surface/Pendant 2000 mm



Cross Coupling
60.3036.11



Straight connector
60.3044.14



Attachment on track for wire
suspension
60.3057.11



Connector T – Inside Right
60.3047.29



Connector T – Inside Left
60.3048.11



Dali Flexible connector
60.3037.14ADA



Ceiling fitting with rose
60.3094.14



Ceiling fitting with rose
60.3094.11



Attachment on track for rod
suspension m6 thread
60.3018.14



Conector T – Outside Left
60.3051.29



Attachment on track for rod
suspension m6 thread
60.3018.11



Fix-point
60.3023.29



Power supply rose cover
60.3092.11



Connector 90° Outside
60.3028.29



Lead-weighted wire 1500 mm
60.3095.29



Dali Flexible connector
60.3037.11ADA



Suspension rod with 1m rose. M6
thread
60.3014.14



Blind end
60.3016.11



Connector T – Inside Left
60.3048.14



Connector T – Inside Left
60.3048.29



Corner adjustable connector
60.3046.11



Conector T – Outside Right
60.3049.11



1 m suspension rod with ceiling rose
with m6 thread
60.3097.11



Connector 90° Outside
60.3028.14



Connector 90° Inside
60.3029.14



Bracket
60.3025.29



Lead-weighted wire 3000 mm
60.3096.29



1 m suspension rod with ceiling rose
with m6 thread
60.3097.14



Bracket
60.3025.14



Mean connector
60.3043.14



Corner adjustable connector
60.3046.29



Cross Coupling
60.3036.14



Conector T – Outside Left
60.3051.11



Live end left
60.3039.12



Corner adjustable connector
60.3046.14



Live end right
60.3038.14



Live end right
60.3038.11



Straight connector
60.3044.12



Connector 90° Outside
60.3028.11



Bracket
60.3025.11



Live end right
60.3038.12



Straight connector
60.3044.11



Suspension rod with 1m rose. M6
thread
60.3014.11



Recessed box for fix-point
60.3022.11



Live end left
60.3039.11



Blind end
60.3016.14

Dali Flexible connector
60.3037.29ADA

Connector 90° Inside
60.3029.29



Attachment on track for wire
suspension
60.3057.29



Connector T – Inside Right
60.3047.11



Cross Coupling
60.3036.29



Mean connector
60.3043.11



Fix-point
60.3023.11



Bracket for fixing track to wall or
ceiling
60.3093.29



Complete wall support 70 mm
60.3083.29



Conector T – Outside Right
60.3049.14



Mean connector
60.3043.29



Connector T – Inside Right
60.3047.14



Live end left
60.3039.14



Recessed box for fix-point
60.3022.14



Fix-point
60.3023.14



Flexible suspension kit
60.3008.14



Connector 90° Inside
60.3029.11



Blind end
60.3016.12



Flexible suspension kit
60.3008.11



Lead bending key
60.3054



