



Three Phase Track Surface/Pendant 4000 mm

■ 60.3104.11 - Matt White

GLOBALTRACK offers benefits for advanced installations: the main connectors are feedable and the feeding cable can be hidden under the elegant suspension accessories. GLOBALTRACK lighting tracks are designed for easy surface mounting on ceilings and walls, or recessed mounting in suspended ceilings. Lighting tracks can be suspended at any desired height.

Main specifications

Mountings	Surface and suspension
Environment	Indoor dry location

Electrical

Emergency	Without
Insulation class	I

Physical

Color	Matt White
Weight (kg)	3.20
Length (mm)	4000



Three Phase Track Surface/Pendant 4000 mm



Complete wall support 70 mm
60.3083.29



Dali Flexible connector
60.3037.29ADA



Attachment on track for rod
suspension m6 thread
60.3018.11



Mean connector
60.3043.11



Suspension rod with 1m rose. M6
thread
60.3014.11



Attachment on track for wire
suspension
60.3057.11



Corner adjustable connector
60.3046.11



Straight connector
60.3044.12



Bracket
60.3025.14



Live end left
60.3039.11



Blind end
60.3016.14



Attachment on track for rod
suspension m6 thread
60.3018.14



Suspension rod with 1m rose. M6
thread
60.3014.14



Corner adjustable connector
60.3046.29



Live end left
60.3039.14



Connector T – Inside Right
60.3047.14



Flexible suspension kit
60.3008.14



Dali Flexible connector
60.3037.14ADA



1 m suspension rod with ceiling rose
with m6 thread
60.3097.11



Conector T – Outside Left
60.3051.14



Live end left
60.3039.12



Cross Coupling
60.3036.29



Track cover strip L 3000 mm
60.3090.11



Conector T – Outside Right
60.3049.14



Mean connector
60.3043.14



Flexible suspension kit
60.3008.11



Bracket
60.3025.11



Lead bending key
60.3054



Connector 90° Inside
60.3029.11



Connector T – Inside Left
60.3048.14



Corner adjustable connector
60.3046.14



Connector 90° Outside
60.3028.14



Connector 90° Outside
60.3028.11



Connector T – Inside Right
60.3047.29



Connector 90° Inside
60.3029.14



Straight connector
60.3044.14





Bracket for fixing track to wall or ceiling
60.3093.29



Blind end
60.3016.12



Connector 90° Inside
60.3029.29



Mean connector
60.3043.29



Fix-point
60.3023.14



Recessed box for fix-point
60.3022.14



Live end right
60.3038.12



Live end right
60.3038.11



Attachment on track for wire suspension
60.3057.29



Conector T – Outside Left
60.3051.11



Recessed box for fix-point
60.3022.11



Cross Coupling
60.3036.11



Ceiling fitting with rose
60.3094.11



Connector T – Inside Right
60.3047.11



Dali Flexible connector
60.3037.11ADA



Ceiling fitting with rose
60.3094.14



Connector 90° Outside
60.3028.29



Blind end
60.3016.11



Power supply rose cover
60.3092.11



Bracket
60.3025.29



Live end right
60.3038.14



Straight connector
60.3044.11



Connector T – Inside Left
60.3048.11



Fix-point
60.3023.29



Conector T – Outside Right
60.3049.11



Fix-point
60.3023.11



Conector T – Outside Left
60.3051.29



Cross Coupling
60.3036.14



1 m suspension rod with ceiling rose
with m6 thread
60.3097.14

Connector T – Inside Left
60.3048.29