

Three Phase Track Surface/Pendant 4000 mm

■ 60.3104.14 - Matt Black

GLOBALTRACK offers benefits for advanced installations: the main connectors are feedable and the feeding cable can be hidden under the elegant suspension accessories. GLOBALTRACK lighting tracks are designed for easy surface mounting on ceilings and walls, or recessed mounting in suspended ceilings. Lighting tracks can be suspended at any desired height.

Main specifications




Mountings	Surface and suspension
Environment	Indoor dry location

Electrical

Emergency	Without
Insulation class	I

Physical

Color	Matt Black
Weight (kg)	3.20
Length (mm)	4000



Three Phase Track Surface/Pendant 4000 mm



Mean connector
60.3043.14

Corner adjustable connector
60.3046.29

Connector 90° Outside
60.3028.29



Attachment on track for wire
suspension
60.3057.29

Connector 90° Outside
60.3028.14

Fix-point
60.3023.14



Connector 90° Inside
60.3029.11

Attachment on track for rod
suspension m6 thread
60.3018.11

Connector T – Inside Left
60.3048.29



Bracket
60.3025.14



Conector T – Outside Left
60.3051.14



Mean connector
60.3043.11



Blind end
60.3016.12



Corner adjustable connector
60.3046.14



Conector T – Outside Left
60.3051.29



Corner adjustable connector
60.3046.11



Cross Coupling
60.3036.14



Connector 90° Inside
60.3029.14



Flexible suspension kit
60.3008.11



Fix-point
60.3023.11



Live end right
60.3038.11



Dali Flexible connector
60.3037.14ADA



Connector 90° Inside
60.3029.29



Straight connector
60.3044.11



Blind end
60.3016.14



Bracket
60.3025.29



Live end left
60.3039.12



Track cover strip L 3000 mm
60.3090.11

Blind end
60.3016.11

1 m suspension rod with ceiling rose
with m6 thread
60.3097.11



Complete wall support 70 mm
60.3083.29



Mean connector
60.3043.29



Live end left
60.3039.11



Connector T – Inside Right
60.3047.11



Recessed box for fix-point
60.3022.11



1 m suspension rod with ceiling rose
with m6 thread
60.3097.14



Conector T – Outside Right
60.3049.14



Lead-weighted wire 1500 mm
60.3095.29



Lead-weighted wire 3000 mm
60.3096.29



Attachment on track for wire
suspension
60.3057.11



Dali Flexible connector
60.3037.11ADA



Connector T – Inside Right
60.3047.29



Attachment on track for rod
suspension m6 thread
60.3018.14



Cross Coupling
60.3036.11



Straight connector
60.3044.12



Live end left
60.3039.14



Live end right
60.3038.14



Conector T – Outside Left
60.3051.11



Connector T – Inside Left
60.3048.14



Recessed box for fix-point
60.3022.14



Dali Flexible connector
60.3037.29ADA



Power supply rose cover
60.3092.11



Connector T – Inside Left
60.3048.11



Connector T – Inside Right
60.3047.14



Cross Coupling
60.3036.29



Lead bending key
60.3054



Fix-point
60.3023.29



Bracket
60.3025.11



Flexible suspension kit
60.3008.14



Live end right
60.3038.12



Ceiling fitting with rose
60.3094.14



Connector 90° Outside
60.3028.11



Ceiling fitting with rose
60.3094.11



Conector T – Outside Right
60.3049.11



Suspension rod with 1m rose. M6
thread
60.3014.14



Suspension rod with 1m rose. M6
thread
60.3014.11

Bracket for fixing track to wall or
ceiling
60.3093.29

Straight connector
60.3044.14