



Three Phase Track Surface/Pendant Dali 1000 mm

■ 60.3101.14ADA - Matt Black

GLOBAL PRO offers benefits for advanced installations: the main connectors are feedable and the feeding cable can be hidden under the elegant suspension accessories. GLOBAL PRO lighting tracks are designed for easy surface mounting on ceilings and walls, or recessed mounting in suspended ceilings. Lighting tracks can be suspended at any desired height. Other advantages of...

GLOBAL PRO offers benefits for advanced installations: the main connectors are feedable and the feeding cable can be hidden under the elegant suspension accessories. GLOBAL PRO lighting tracks are designed for easy surface mounting on ceilings and walls, or recessed mounting in suspended ceilings. Lighting tracks can be suspended at any desired height. Other advantages of the three-circuit system are its high loading capacity and the possibility of forming independent fixture groups in all three circuits. This permits illumination of the most demanding environments.

Main specifications

Mountings	Surface and suspension
Environment	Indoor dry location

Electrical

Emergency	Without
Insulation class	I

Physical

Color	Matt Black
Weight (kg)	0.80
Length (mm)	1000



Three Phase Track Surface/Pendant Dali 1000 mm



Attachment on track for rod suspension m6 thread
60.3018.14



Ceiling fitting with rose
60.3094.14



1 m suspension rod with ceiling rose with m6 thread
60.3097.11



Blind end
60.3016.14



Connector T – Inside Right Dali
60.3047.29ADA



Straight Connector Dali
60.3044.12ADA



Attachment on track for wire suspension
60.3057.29



Connector 90° Inside Dali
60.3029.29ADA



Ceiling fitting with rose
60.3094.11



Power supply rose cover
60.3092.11



Suspension rod with 1m rose. M6
thread
60.3014.11



Connector T – Inside Left Dali
60.3048.11ADA



Attachment on track for rod
suspension m6 thread
60.3018.11



Bracket
60.3025.14



Lead-weighted wire 1500 mm
60.3095.29



Lead-weighted wire 3000 mm
60.3096.29



Blind end
60.3016.12



Cross Coupling Dali
60.3036.14ADA



Suspension rod with 1m rose. M6
thread
60.3014.14



Connector 90° Outside Dali
60.3028.29ADA



Complete wall support 70 mm
60.3083.29



Bracket for fixing track to wall or
ceiling
60.3093.29



Flexible suspension kit
60.3008.14



Mean connector Dali
60.3043.29ADA



Mean connector Dali
60.3043.14ADA



Attachment on track for wire
suspension
60.3057.11



Mean connector Dali
60.3043.11ADA



Bracket
60.3025.29



Connector T – Inside Left Dali
60.3048.14ADA



Connector T – Inside Right Dali
60.3047.11ADA



Bracket
60.3025.11



1 m suspension rod with ceiling rose
with m6 thread
60.3097.14



Connector 90° Outside Dali
60.3028.14ADA



Straight Connector Dali
60.3044.11ADA



Connector 90° Outside Dali
60.3028.11ADA



Connector 90° Inside Dali
60.3029.11ADA



Connector T – Inside Left Dali
60.3048.29ADA



Track cover strip L 3000 mm
60.3090.11



Blind end
60.3016.11



Cross Coupling Dali
60.3036.29ADA



Lead bending key
60.3054



Flexible suspension kit
60.3008.11



Cross Coupling Dali
60.3036.11ADA

Connector T – Inside Right Dali
60.3047.14ADA

Connector 90° Inside Dali
60.3029.14ADA



Straight Connector Dali
60.3044.14ADA