



## Three Phase Track Surface/Pendant Dali 2000 mm

### ■ 60.3102.14ADA - Matt black



GLOBAL PRO offers benefits for advanced installations: the main connectors are feedable and the feeding cable can be hidden under the elegant suspension accessories. GLOBAL PRO lighting tracks are designed for easy surface mounting on ceilings and walls, or recessed mounting in suspended ceilings. Lighting tracks can be suspended at any desired height. Other advantages of...

GLOBAL PRO offers benefits for advanced installations: the main connectors are feedable and the feeding cable can be hidden under the elegant suspension accessories. GLOBAL PRO lighting tracks are designed for easy surface mounting on ceilings and walls, or recessed mounting in suspended ceilings. Lighting tracks can be suspended at any desired height. Other advantages of the three-circuit system are its high loading capacity and the possibility of forming independent fixture groups in all three circuits. This permits illumination of the most demanding environments.

### Main specifications

<b>Mountings</b>	Surface and suspension
<b>Environment</b>	Indoor

### Electrical

<b>Emergency Insulation class</b>	Without I
-----------------------------------	-----------

### Physical

<b>Color</b>	Matt black
<b>Weight (kg)</b>	0.80
<b>Length (mm)</b>	2000



## Three Phase Track Surface/Pendant Dali 2000 mm



---

Ceiling fitting with rose  
60.3094.11



---

Ceiling fitting with rose  
60.3094.14



---

Attachment on track for rod  
suspension m6 thread  
60.3018.11



---

Attachment on track for rod  
suspension m6 thread  
60.3018.14



---

Lead-weighted wire 1500 mm  
60.3095.29



---

Lead-weighted wire 3000 mm  
60.3096.29



---

Bracket  
60.3025.29



---

Bracket  
60.3025.14



---

Bracket  
60.3025.11



---

Bracket for fixing track to wall or ceiling  
60.3093.29



---

Attachment on track for wire suspension  
60.3057.11



---

Attachment on track for wire suspension  
60.3057.29



---

Complete wall support 70 mm  
60.3083.29



---

Power supply rose cover  
60.3092.11



---

Mean connector Dali  
60.3043.11ADA



---

Mean connector Dali  
60.3043.14ADA



---

Mean connector Dali  
60.3043.29ADA



---

Connector 90° Inside Dali  
60.3029.11ADA



---

Connector 90° Inside Dali  
60.3029.14ADA



---

Connector 90° Inside Dali  
60.3029.29ADA



---

Connector 90° Outside Dali  
60.3028.11ADA



---

Connector 90° Outside Dali  
60.3028.14ADA



---

Connector 90° Outside Dali  
60.3028.29ADA



---

Connector T – Inside Right Dali  
60.3047.11ADA



---

Connector T – Inside Right Dali  
60.3047.14ADA



---

Connector T – Inside Right Dali  
60.3047.29ADA



---

Connector T – Inside Left Dali  
60.3048.11ADA



---

Connector T – Inside Left Dali  
60.3048.14ADA



---

Connector T – Inside Left Dali  
60.3048.29ADA



---

Cross Coupling Dali  
60.3036.11ADA





---

Cross Coupling Dali  
60.3036.14ADA



---

Cross Coupling Dali  
60.3036.29ADA



---

Track cover strip L 3000 mm  
60.3090.11



---

Blind end  
60.3016.11



---

Blind end  
60.3016.14



---

Blind end  
60.3016.12



---

Straight Connector Dali  
60.3044.11ADA



---


Straight Connector Dali  
60.3044.14ADA



---

Straight Connector Dali  
60.3044.12ADA





Suspension rod with 1m rose. M6 thread

60.3014.11



Suspension rod with 1m rose. M6 thread  
60.3014.14

Lead bending key  
60.3054

1 m suspension rod with ceiling rose with m6 thread  
60.3097.11



1 m suspension rod with ceiling rose with m6 thread  
60.3097.14