



## Three Phase Track Surface/Pendant Dali 4000 mm

### 60.3104.11ADA - Matt White



GLOBAL PRO offers benefits for advanced installations: the main connectors are feedable and the feeding cable can be hidden under the elegant suspension accessories. GLOBAL PRO lighting tracks are designed for easy surface mounting on ceilings and walls, or recessed mounting in suspended ceilings. Lighting tracks can be suspended at any desired height. Other advantages of...

GLOBAL PRO offers benefits for advanced installations: the main connectors are feedable and the feeding cable can be hidden under the elegant suspension accessories. GLOBAL PRO lighting tracks are designed for easy surface mounting on ceilings and walls, or recessed mounting in suspended ceilings. Lighting tracks can be suspended at any desired height. Other advantages of the three-circuit system are its high loading capacity and the possibility of forming independent fixture groups in all three circuits. This permits illumination of the most demanding environments.

### Main specifications

<b>Mountings</b>	Surface and suspension
<b>Environment</b>	Indoor dry location

### Electrical

<b>Emergency</b>	Without
<b>Insulation class</b>	I

### Physical

<b>Color</b>	Matt White
<b>Weight (kg)</b>	0.80
<b>Length (mm)</b>	4000



## Three Phase Track Surface/Pendant Dali 4000 mm



---

Connector 90° Outside Dali  
60.3028.29ADA



---

Attachment on track for wire  
suspension  
60.3057.29



---

Lead-weighted wire 3000 mm  
60.3096.29



---

Connector T – Inside Right Dali  
60.3047.14ADA



---

Straight Connector Dali  
60.3044.14ADA



---

Blind end  
60.3016.11



---

Flexible suspension kit  
60.3008.14



---

Bracket  
60.3025.11



---

Mean connector Dali  
60.3043.14ADA



Cross Coupling Dali  
60.3036.11ADA



Flexible suspension kit  
60.3008.11



Track cover strip L 3000 mm  
60.3090.11



Connector T – Inside Left Dali  
60.3048.11ADA



Connector 90° Inside Dali  
60.3029.29ADA



Lead-weighted wire 1500 mm  
60.3095.29



Suspension rod with 1m rose. M6  
thread  
60.3014.14



Attachment on track for rod  
suspension m6 thread  
60.3018.11



Ceiling fitting with rose  
60.3094.11



---

Ceiling fitting with rose  
60.3094.14



Connector 90° Inside Dali  
60.3029.11ADA



Connector T – Inside Right Dali  
60.3047.29ADA



---

Connector 90° Outside Dali  
60.3028.11ADA



Connector 90° Inside Dali  
60.3029.14ADA



Mean connector Dali  
60.3043.29ADA



---

Complete wall support 70 mm  
60.3083.29



1 m suspension rod with ceiling rose  
with m6 thread  
60.3097.14



Attachment on track for rod  
suspension m6 thread  
60.3018.14



---

Connector T – Inside Right Dali

Blind end

Bracket for fixing track to wall or

---



1 m suspension rod with ceiling rose  
with m6 thread  
60.3097.11



Suspension rod with 1m rose. M6  
thread  
60.3014.11



Connector T – Inside Left Dali  
60.3048.29ADA



Straight Connector Dali  
60.3044.11ADA



Mean connector Dali  
60.3043.11ADA



Blind end  
60.3016.12



Attachment on track for wire  
suspension  
60.3057.11



Lead bending key  
60.3054



Connector 90° Outside Dali  
60.3028.14ADA



---

Bracket  
60.3025.29



---

Power supply rose cover  
60.3092.11



---

Connector T – Inside Left Dali  
60.3048.14ADA



---

Straight Connector Dali  
60.3044.12ADA



---

Bracket  
60.3025.14



---

Cross Coupling Dali  
60.3036.14ADA



---

Cross Coupling Dali  
60.3036.29ADA