


## Tubular Bells Pro Ceiling

Surface luminaire to be installed on ceiling for led. phosphor led module integrated. electronic transformer 220/240V integrated.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	394
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling surface
<b>Power (W)</b>	7.4W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	98		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Phosphor LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	32
<b>Beam angle C90-270 (°)</b>	32



<b>Beam Angle:</b>	32°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	1227	0.58	
2	307	1.16	
3	136	1.73	
4	77	2.31	
5	49	2.89	

Luminous flux luminaire  
394 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	I
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Electronic		

### Physical

<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	0.85

### Certification / Marking

